

GAS DIFFUSER STONES

FOR FOAMING TEST

ENGINEERED TO ASTM STANDARD

Foaming characteristics is an important criterion to select lubricating oils for high-speed gears and high-volume pumps. Inadequate lubrication, cavitation, and overflow loss of lubricant can lead to mechanical failure. Oil foaming tendency can be measured with equipment that use standardized procedures, such as ASTM D892. Foaming of engine coolants is tested using D1881 method. Foam testing equipment require a means to diffuse controlled volume of gas in oil or coolant.

ALUNDUM® - POROUS SPHERE

- Fused Alumina grains held together by a porcelain bond
- Volume & size of pores are controlled during manufacturing to allow consistent gas flow
- Available as Rated (certified to D892) or Un-rated



USED IN FOAM
TESTERS FOR OVER
30 YEARS

BENEFITS



Controlled volume of gas flow
through pores of the sphere



Can be re-used



Proven material technology

Leverage Our Expertise.

Saint-Gobain Performance Ceramics & Refractories engineers and researchers collaborate with you, our customers, to solve operational challenges with labware products.

For more information:

www.ceramicsrefractories.saint-gobain.com
ceramics.refractories@saint-gobain.com

Follow us on 



The information contained in this document is believed to be accurate and reliable but is provided without guarantee or warranty on the part of Saint-Gobain Performance Ceramics & Refractories. Process parameters and requirements can impact typical values and test methods. Further, nothing present herein should be interpreted as an authorization or inducement to practice any patented invention without an appropriate license. Saint-Gobain Performance Ceramics & Refractories Terms and Conditions apply to all purchases.

Copyright © 2024, Saint-Gobain Performance Ceramics & Refractories. All rights reserved.